

255 Control Valves



2

- 760 Demand
- Simple, economic electronic demand (volumetric)
- Calendar override
- 12-volt operation
- 28-day variable reserve
- High efficiency regeneration sequence
- Automatic capacity calculations
- Operates 255, 263, 268 with one controller

Pentair Water[®] offers a full range of Autotrol[®] Control Valves to meet all residential water conditioning applications.

Logix[™] Series

740 Time Clock

- Simple, economic electronic time clock (chronometric)
- 7- or 99-day regeneration setting
- High efficiency regeneration sequence
- 12-volt operation
- Filter or conditioner setting in one control
- Operates 255, 263, 268 with one controller

762 Demand

Same features as the 760, plus:

- Fully programmable cycle times
- Salt setting in 1-pound increments
- Optional no-salt detector
- Operates 255, 263, 268, 278, and Magnum IT with one controller

742 Time Clock

Same features as the 740 Time Clock, plus:

- Fully programmable cycle times
- Salt setting in 1-pound increments
- Optional no-salt detector
- Operates 255, 263, 268, 278, and Magnum[®] IT with one controller

764 Demand

Same features as the 762, plus:

- Multi-tank applications (twin alternating, multitank parallel)
- Control lockout
- Remote regeneration



RESIDENTIAL CONTROL VALVES

255 Control Valves

Electrical

Controller Operating Voltage Input Supply Frequency Motor Input Voltage Controller System Power Consumption 12 Volt – AC (Requires use of Pentair Water®-supplied transformer)
50 or 60 Hz (Controller configuration dependent)
12 Volt – AC
3 Watts average

Transformer – All Controllers

All Controllers require the use of a Pentair Water-supplied transformer.

Transformer Output Voltage	
Transformer Input Options	
Transformer Plug Options	

12 Volt – AC 400mA		
115 Volt – AC 50/60	Hz; 230 Volt – A0	C 50/60 Hz; 100 Volt – AC 50/60 Hz
Indoor North Americ	an Plug	Taiwan/Korea Plug
Outdoor North Ame	rican	Australian Plug
(UL Listed for outdo	or use)	United Kingdom Plug
Japanese Plug		Mainland Europe Plug

Additionagd Kingdom Plug

Injector* Performance Logix™



20580 Enterprise Avenue Brookfield, WI 53045 Tel: 262.784.4490 Fax: 262.784.7794

Customer Care: 800.279.9404

5730 North Glen Park Road Milwaukee, WI 53209 Tel: 262.238.4400 Fax: 262.238.4402 ©2010 Pentair Residential Filtration, LLC 1018069 Rev D FE10

: 800.279.9404 www.pentairwatertreatment.com